

BRO-CURE

Chemically reactive, silicate based, concrete curing, hardening and sealing compound.

HOW IT WORKS

BRO-CURE chemically reacts with new and old concrete to cure, harden and dustproof without changing the normal concrete surface texture.

APPLICATIONS

- ◆ Use on concrete surfaces that are to receive further treatment and where water curing, burlap or polyethylene are not viable alternatives.
- ◆ Use to harden older, porous concrete to minimize surface dust caused by abrasion and carbonation.
- ◆ Use on concrete surfaces in parking garages that are to receive sealers, joint sealants or traffic topping membranes; use on precast "T" beam surfaces that are to receive a bonded concrete topping; and, use on floors and walls that are to receive paints, coatings, grouts, seamless quartz flooring or other surface treatments.

ADVANTAGES

- ◆ Leaves no residue and will not impair the application, penetration or adhesion of subsequently applied surface treatments. Eliminates the need for mechanical or chemical removal.
- ◆ Concrete surface texture is not affected which means skidding and slipping is minimized. This is especially important on horizontal decks that will be exposed to foot or vehicular traffic within a few days following application.
- ◆ Improves concrete's resistance to acidic compounds and staining.
- ◆ Increases compressive strength and reduces surface crazing and cracking.
- ◆ Sprays easily.
- ◆ Contains no hydrocarbon solvents.
- ◆ Costs less than membrane cures.
- ◆ Contains a red fugitive dye for easy, uniform application.
- ◆ Also available in a concentrated version which requires dilution (BRO-CURE CONCENTRATE).
- ◆ Meets all federal and state VOC requirements.

PRECAUTIONS

- ◆ When applied before the final troweling, BRO-CURE may accelerate initial set. Allow ample time for the finishers to complete their work. Reapply BRO-CURE after finish troweling the concrete.
- ◆ If BRO-CURE comes into contact with glass, marble-like surfaces or unfinished metal such as aluminum, flush immediately with water. BRO-CURE is not removable after one hour and may permanently etch these surfaces.
- ◆ Avoid skin and eye contact with BRO-CURE.

USE INSTRUCTIONS

- ◆ Request current product literature, labels and material safety data sheets from manufacturer and read thoroughly before product use.
- ◆ Site environmental conditions, substrate conditions and construction have a major effect on product selection, application methods, procedures and rates, appearance and performance. Product literature provides general information applicable to some conditions. However, an adequate site test by the purchaser or installer in advance of field scale dilution or use is mandatory (irrespective of any other verbal or written representations) to verify product and quantities purchased can be satisfactorily applied and will achieve desired appearance and performance under intended use conditions.
- ◆ BRO-CURE is ready to use. Do not dilute. BRO-CURE CONCENTRATE is shipped in short-filled containers and requires dilution by filling the containers full with water. BRO-CURE CONCENTRATE should be well mixed before use and before each withdrawal from original container. Use NOX-CRETE'S specially designed drum agitator for mixing 55-gallon drums.
- ◆ Apply with either handpump or power spray equipment, such as NOX-CRETE'S PEPECT FORM & CONCRETE SPRAYER, IDEAL FORM & CONCRETE SPRAYER or THE PERFECT POWER SPRAYER. The equipment must be clean and free of any solvent or oil based materials. Wash equipment with clean water immediately after using.

BRO-CURE

3

cures, sealers & hardeners



chemical solutions to concrete problems

- ◆ Apply immediately after final troweling. For best results apply at rate of 350-450 sf/gal (8.6-11.0 sm/l) in one uniform coat. Use NOX-CRETE'S MONOFILM immediately after screeding or after the first floating operation on hot and windy days to restrict early moisture loss and resulting surface cracks.

TECHNICAL DATA

Viscosity Water Thin
Freeze Point 32° F (0° C)
Flash Point Not Combustible
VOC 0 g/l

PACKAGING

Product is packaged in 5 gal. (19.0 l) / 49 lbs. (22.3 kg) pails and 55 gal. (208 l) / 526 lbs. (239 kg) drums.

SHELF LIFE

One year in original factory sealed containers. Use before expiration date listed on container.

HANDLING/STORAGE

Read Material Safety Data Sheet (MSDS) prior to using. Protect from freezing. Exposure to freezing temperatures will necessitate agitation prior to use and may result in expansion and subsequent rupture of container.

AVAILABILITY & TECHNICAL SERVICES

In addition to corporate offices in Omaha, Nebraska, NOX-CRETE Products Group maintains regional offices and distribution centers in principal markets throughout the world. For source or technical information, phone (800) 669-2738 or (402) 341-1976.

LIMITED WARRANTY

NOTICE-READ CAREFULLY

CONDITIONS OF SALE

NOX-CRETE offers this product for sale subject to, and Buyer and all users are deemed to have accepted, the following conditions of sale and limited warranty which may only be varied by written agreement of a duly authorized corporate officer of NOX-CRETE. No other representative of or for NOX-CRETE is authorized to grant any warranty or to waive limitation of liability set forth below.

WARRANTY LIMITATION

NOX-CRETE warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, NOX-CRETE will replace the defective product with new product without charge to the purchaser.

NOX-CRETE makes NO OTHER WARRANTY, either express or implied, concerning this product. There is NO WARRANTY OF MERCHANTABILITY. In no case shall NOX-CRETE be liable for special, indirect or consequential damages resulting from the use or handling of the product and no claim of any kind shall be greater in amount than the purchase price of the product in respect of which damages are claimed.

INHERENT RISKS

NOX-CRETE MAKES NO WARRANTY WITH RESPECT TO THE PERFORMANCE OF THE PRODUCT AFTER IT IS APPLIED BY THE PURCHASER, AND PURCHASER ASSUMES ALL RISKS ASSOCIATED WITH THE USE OR APPLICATION OF THE PRODUCT.